



Description

- Maximum load of 192W (Two 96W Outputs)
- Class 2 Transformer
- ETL Listed
- 24VDC Output
- Dimmable with any standard MLV Triac Dimmer.
- Flicker-Free dimming
- Auto-reset circuit breakers
- Nema 3R enclosure suitable for outdoor use
- 2 knock-outs

Transformer Properties

| | |
|------------|--------------------|
| Dimensions | 9.8" x 4.2" x 3.2" |
| Weight | 140 Oz. |

Electrical Properties

| | |
|-----------------------------|--------------------------------|
| Input Voltage | 120V AC |
| Max Load | 96W Per Port x 2 |
| Input Current Full Load | 2.2 A |
| Output Voltage Full Load | 22.1V DC |
| Max Outpt Current Full Load | 4.31 A Per Port |
| Open Circuit Output Voltage | 24.5V DC |
| Efficiency on I | 84.3% |
| Power Factor | 0.93 |
| Coil Former | Double Section Bobbin |
| Thermal Class | B130°C |
| Leads Primary | PVC 600V #20 |
| Leads Secondary | PVC 300V #14 |
| Circuit Breaker | Primary & Secondary Auto Reset |

Order Code

LP - TR - 192 - 24DC - DIM

Notes

- Must be installed by licensed electrical contractor.

* Please contact for availability